

# ACU-COMMS COMMUNICATIONS CONDUIT

## PRODUCT FACT SHEET



### PRODUCT DESCRIPTION

#### Acu-Comms

CWJ

Acu-Comms conduit provides superior mechanical protection to fragile cable materials like fibre optic and coaxial cables, as well as protection from moisture or chemicals.

Suitable for replacement projects or future installations of additional cable or sub-duct, its flexibility and availability in continuous coiled lengths facilitates easy installation below ground by a variety of methods, including directional drilling, ploughing, and open trench.



CODE	SIZE	WALL THICKNESS (MM)	INSIDE DIAMETER (MM)	LENGTH (M)	COIL DIMENSIONS (MM)			WEIGHT (KG)
					OD	ID	WIDTH	
CWJ03212150	32mm	2.6	27.0	150m Coil	1230	880	280	0.2 kg/m
CWJ06313140	63mm	5.0	53.3	140m Coil	1700	1030	400	0.9 kg/m
CWJ06313200	63mm	5.0	53.3	200m Coil	1900	1030	400	0.9 kg/m
CWJ11013100	110mm	8.6	93.3	100m Coil	2760	2000	470	2.6kg/m
CWJ12513100	125mm	9.8	106.1	100m Coil	2900	2000	530	3.4 kg/m

Manufactured to SDR 13.6.

Dimensions are nominal only.

White co-extruded outer layer for easy identification.

Manufactured in Australia to standard AS/NZS 4130 'Polyethylene (PE) pipes for pressure applications' (dimensions only) and AS/NZS 4129 'Fittings for polyethylene (PE) pipes for pressure applications'.

ISO9001 Quality Management System Certification.

ACU-TECH PIPING SYSTEMS | ABN: 68 626 756 223

Contact us today | P: 1300 270 270 | E: sales@acu-tech.com.au